


ENVIRONMENTAL CONTROL SYSTEM

Ducted environmental control system

/ Model
ECS-36T

MilAIR



/ 36,000 Btu/h
(10.6 kW)

Cooling Capacity

/ 125 °F
(51.7 °C)

Design Ambient Cooling

/ 40 °F
(4.4 °C)

Minimum Ambient Cooling


These units have been designed and tested for use on shelters, vans, and trailers that are subject to demanding transport and environmental conditions. All systems can be modified to meet your specific requirements.

MilAIR's standard product line of unitary ducted systems provide complete environmental control including cooling, heating, ventilation, dehumidification, and filtering.

Please contact sales@milairinc.com
for additional information and options.

Ducted environmental control system

/ Model
ECS-36T



Standard Features

- Sealed Motors
- Refrigerant Access Valves
- Lifting Rings
- Fork Pockets
- Man-Lift Transport Handles
- Remote Control Cable (30 ft.)
- Power Cable (25 ft.)
- Supply/Return Flex Ducts, 12" Dia. x 15 ft. long
- Washable Metal Return & Fresh Air Filter
- Refrigerant Sight Glass
- Hot Gas Bypass (HGB)
- Hour Meter

Options

- Finish to Specification
- Phase Monitor
- Coil Corrosion Protection

Characteristics

Refrigerant	R407c
Compressor	Hermetic Scroll Type
Evaporator Coil	Alum. Fin/Copper Tube
Condenser Coil	Alum. Micro-Channel
Circulating Fan	Motorized Impeller
Condenser Fan	Propeller
Size (L x W x H)	43.00" x 34.00" x 38.00" 109.2 cm x 86.4 cm x 96.5 cm
Frame & Panels	Aluminum
Weight	450 lbs. (204 kg)
Remote Control Panel	Cool/Vent/Off/Heat Thermostat Temp Control Fault Indicator

Performance

Cooling Capacity	36,000 Btu/h (10.6 kW)
Design Ambient Cooling	125 °F (51.7 °C)
Minimum Ambient Cooling	40 °F (4.4 °C)
Total Heating Capacity	25,500 Btu/hr (7.5 kW)
Minimum Ambient Heating	-50 °F (-45.6 °C)
Supply Air Flow Rate	1300 CFM (36.8 CMM)
Evaporator Static Pressure	2.0 Inch Water
Fresh Air Flow Rate	0 - 325 CFM (9.2 CMM)

Electrical

Input Voltage	208 VAC
Number of Phases	3Φ
Frequency	60 Hz
Max Power Consumption	9.5 kW
Wires	3-Wire + GND

Trusted Partner.

Horstman United States

44215 Phoenix Drive,
Sterling Heights, MI 48314

P +1 (586) 737-2100
E sales@milairinc.com

Details provided about the properties and usability of the products are purely for information purposes and do not constitute a guarantee of these characteristics. The extent of goods delivered is determined by the subject matter of the specific contract. No liability accepted for errors or omissions. Subject to technical alterations. © HORSTMAN 2023